



Mastercool[®] Inc.
"World Class Quality"

1 ASPEN DRIVE, RANDOLPH, NJ 07869
PHONE: 973-252-9119 / FAX: 973-252-2455
WEB: WWW.MASTERCOOL.COM

70079 ADJUSTABLE TORQUE WRENCH



SPECIFICATIONS:

- 9 mm x 12 mm interchangeable head
- 17 1/2" (44.5 cm) long handle
- Torque range: 7 ft-lbs (10 N-m) to 81 ft-lbs (110 N-m)
- Open end material: 40 CRV
- Open end hardness: HRC 38-45
- Open end max range: 38 mm
- Overall length: 550 mm
- Accuracy: $\pm 3\%$
- Laser etching
- Meets ASME B107.300 & ISO 6789

Mastercool's Torque Wrench with removable head, features an adjustable head for hex nuts and fasteners up to 1.5" (38mm).

To adjust torque, simply lift, hold the lock, and twist for quick and secure settings. The easy-to-read markings ensure precise adjustments, while the long handle provides enhanced control during use.

Packaged in a blow molded case the 70079 Adjustable Torque Wrench includes a factory calibration certificate.

- OFFICIAL FACTORY CALIBRATION CERTIFICATE provided with every unit
- ACCURACY DEVIATION within $\pm 3\%$ after 10,000-cycle lifespan test at 60% torque load (twice the duration of ISO 6789 standard)
- SAFETY PUSH BUTTON ensures safe and proper operation
- ERGONOMICALLY DESIGNED HANDLE reduces effort and provides a comfortable grip
- CR-V STEEL TUBE offers excellent impact resistance
- SUPERIOR RESISTANCE TO ELASTIC FATIGUE provided by specially designed compression springs