



Mastercool®
"World Class Quality"

1 ASPEN DRIVE, RANDOLPH, NJ 07869
PHONE: 973-252-9119 / FAX: 973-252-2455
WEB: WWW.MASTERCOOL.COM

69395 SPARK FREE TWIN TURBO COMBUSTIBLE GAS RECOVERY MACHINE



SPECIFICATIONS:

- Voltage: 115 V / 60 Hz
- Compressor Power: Spark Free ½ HP dual piston oil-less compressor
- Operating Temperature: 32 to 122°F
- Material: High-Density Polyethylene (HDPE) hard plastic case
- Compatible Refrigerants: All CFC, HCFC, HFC's and A2L and A3 flammable refrigerants
- Recovery Rate: R410A
Direct vapor up to 0.70 lb/min
Direct liquid up to 7.7 lb/min
Push pull up to 20.2 lb/min
- Fittings: ¼" flare

**APPROVED FOR ALL
AIR CONDITIONING REFRIGERANTS
INCLUDING A2L AND A3
FLAMMABLE REFRIGERANTS**

Maximum Recovery. Spark Free. Built for the Toughest Jobs.

Mastercool's 69395 Spark Free Twin Turbo Combustible Gas Recovery Machine is built specifically to handle combustibles and standard refrigerants in HVAC and automotive systems. Its spark free components are optimized for efficiency and ensure safe operation when working with flammable refrigerants. With recovery rates among the highest in the industry the 69395 meets the demands of rigorous refrigerant recovery tasks.

The enhanced internal structure of Mastercool's Spark Free Twin Turbo Combustible Gas Recovery Machine allows for maximum recovery capacity while at the same time decreasing size and weight. The design of the spark free dual piston oil-less compressor provides maximum recovery efficiency while the high-volume cooling fan and condenser ensures optimal cooling efficiency which keeps the compressor working at higher capacities. A safety high pressure cut-off switch automatically stops operation if pressure levels exceed safe limits while the purge valve ensures 100% refrigerant removal from the condenser and recovery machine. Encased in a durable, reinforced plastic shell, Mastercool's Spark Free Twin Turbo Combustible Gas Recovery Machine is engineered to endure challenging work environments, all while delivering fast and efficient performance.

FEATURES:

- SPARK FREE COMPONENTS ensures safe operation even when working with flammable refrigerants complying with industry standards
- SAFETY HIGH PRESSURE CUT-OFF SWITCH automatically stops operation if pressure levels exceed safe limits which protects both the user and the equipment
- SPARK-FREE DUAL PISTON OIL-LESS COMPRESSOR delivers maximum recovery efficiency while reducing size and weight while delivering safe recovery of R1234yf refrigerants
- HIGH VOLUME COOLING FAN prevents overheating and ensures a consistent performance in high-temperature environments
- LARGEST VOLUME RECOVERY RATE in the market allowing technicians to handle demanding jobs
- WORKS WITH ALL REFRIGERANTS including CFCs, HCFCs, HFCs and A2L and A3 flammable refrigerants making it ideal for HVAC and automotive recovery tasks
- PURGE VALVE for full refrigerant removal
- SEALED CRANK CASE eliminates refrigerant loss during the recovery process
- DURABLE AND PORTABLE with its injection molded high density polyethylene case and built-in bumper guards for enhanced impact resistance