



The One You Reach For

70079-DIG


Digital Adjustable Torque Wrench



**FACTORY
CALIBRATED**



**±2%
PROFESSIONAL
ACCURACY**



**0-38 MM
ADJUSTABLE
JAW**



**LED & VIBRATION
TORQUE ALERTS**

SPECIFICATIONS:

- **Torque Range:** 6.8–135 N·m (5–100 ft-lb)
- **Display:** Digital torque value readout
- **Accuracy (Clockwise):** ±2% of reading
- **Accuracy (Counterclockwise):** ±3% of reading
- **Measurement Modes:** Peak Hold and Track modes
- **Torque Alert Indicators:** LED collar and vibration alert when target torque is reached
- **Controls:** 5-button interface
- **Selectable Units:** N·m, ft-lb, in-lb, kg-cm
- **Display Size:** 33 mm × 15 mm widescreen LCD
- **Display Viewing Angle:** Up to 135° readability
- **Memory Capacity:** Stores up to 1,000 measurements
- **Preset Capacity:** 9 programmable preset torque values
- **Battery Life:** Up to 50 hours of continuous operation with backlight enabled
- **Electronics:** High-quality PCB for improved accuracy, stability, and sensitivity
- **Operating Temperature:** -30°C to 60°C (-22°F to 140°F)
- **Auto Power-Off:** After 5 minutes of inactivity
- **Battery Type:** 2 × AAA batteries (included)
- **Open-End Wrench Capacity:** Adjustable jaw opening 0 – 38 mm
- **Drive Connection:** 9 × 12 mm male square adapter
- **Calibration Reference:** Torque calibration point marked on handle
- **Standards Compliance:** Meets ASME B107.300 requirements
- **Dimensions:** 355 × 40 mm (includes the adjustable open wrench head)
- **Weight:** 500 g + adjustable head 212 g

THE MOST ADVANCED ADJUSTABLE DIGITAL TORQUE WRENCH IN ITS CLASS

Mastercool's Digital Adjustable Torque Wrench is a professional-grade digital adjustable torque wrench designed for HVAC/R technicians to accurately tighten flare nuts and fittings to manufacturer specifications. Featuring a wide 135° viewing angle display, LED collar and vibration alerts, 9 programmable preset torque settings, 1000-reading memory capacity, and a heavy-duty 0 – 38 mm adjustable jaw, it delivers precision, consistency, and ease of use in the field.

- **OFFICIAL FACTORY CALIBRATION CERTIFICATE** provided with every unit
- **Wide Torque Range (6.8–135 N·m):** Covers a broad range of HVAC/R flare nut and fitting applications with a single tool.
- **Heavy-Duty Adjustable Jaw (0–38 mm):** Accommodates a wider range of fitting sizes than many competing digital torque wrenches.
- **LED Collar & Vibration Alerts:** Provides clear visual and tactile feedback when the target torque is reached, helping prevent over-tightening.
- **Wide 135° Viewing Angle Display:** The large digital display is easy to read from multiple angles, improving visibility in tight or awkward working positions.
- **9 Preset Torque Settings:** Save up to nine frequently used torque values for faster, more consistent installations.
- **1000 Reading Memory Capacity:** Stores torque data for reference and record keeping.
- **Professional Accuracy:** ±2% Clockwise (CW) and ±3% Counterclockwise (CCW) operation helps ensure fittings are tightened to manufacturer specifications.
- **Multiple Engineering Units:** Easily switch between N·m, ft-lb, in-lb, and kg-cm.